

Splitters, taps and optical cables

Characterised by their compact size, the Home Fibre splitters and taps distribute signals throughout the building on a single-mode fibre optic cable (operating wavelength 1260nm - 1590nm).

The innovative "MINI" optical connector, just 3mm in diameter, ensures easy wiring in any installation environment. The cables are supplied pre-terminated and the optical connections are protected by caps.

A339469 FFO_EN 5/14



"MINI" optical connector
Ø 3mm



Splitters

Item	VOV 2	VOV 4
Fracarro code	287210	287211
Type	1 X 2	1 X 4
Insertion loss	dB	dB
	<3.9	<7.8

Taps - 1 way

Item	VOT 7/3	VOT 8/2	VOT 9/1
Fracarro code	287212	287213	287214
Through loss	dB	dB	dB
	<2.1	<1.5	<0.8
Tap loss	dB	dB	dB
	<6.4	<8.5	<12.7

Taps - 4 ways

Item	VOT 1/2	VOT 2/3	VOT 3/4
Fracarro code	287215	287216	287217
Through loss	dB	dB	dB
	<3.8	<3.1	<2.5
Tap loss	dB	dB	dB
	<11.4	<13.7	<15

Optical cables

Item	Code	Length
PR003	287219	3mt
PR005	287220	5mt
PR010	287221	10mt
PR025	287222	25mt
PR035	287327	35mt
PR050	287328	50mt
PR075	287329	75mt
PR100	287223	100mt

Single mode
pre-terminated fibre
cables of varying
lengths

Mini adapters

Item	Code
Connecting accessories	MIN/MIN 287225
Adapter SC/APC MINI	PR ADAPT 287226
PULL adapter	PULLCON 287224
	OPTATT3dB 287239
Optical attenuators	OPTATT7dB 287238
	OPTATT14dB 287237

Fracarro Home Fibre

4 SAT + DVB-T
over one fibre

Fibre Optic
for DVB-T and SAT
distribution systems
in residential buildings
up to 4 SAT + DVB-T
over just one cable

Fracarro Radioindustrie S.p.A.

Via Cazzaro, 3
31033 Castelfranco Veneto (TV)
Italy
Tel. +39 0423 7361
Fax +39 0423 736220
www.fracarro.com
info@fracarro.com
Società a socio unico

Fracarro Home Fibre

Transmitters

The new Home Fibre optical transmitters work in the 2nd and 3rd optical windows (1310-1600nm) and manage both **SAT signals** - from a traditional 4 LNB and dish combination - including full bandwidth **DVB-T terrestrial signals**. Equipped with automatic gain control (AGC), the solution - based on WDM technology - enables the distribution of up to **4 satellites plus full terrestrial over just one fibre cable**.



	OPT-TX DT	OPT-TX 1510	OPT-TX 1530	OPT-TX 1550	OPT-TX 1570
Fracarro code	270694	270667	270668	270669	270670
Optical output					
Connectors	SC/APC				
Wavelength	1310	1510	1530	1550	1570
Optical power	7.5dBm	9.5dBm	9.5dBm	9.5dBm	9.5dBm
Main features					
Mains	184 - 264/50 - 60Vac/Hz				

WDM Diplexers

WDM diplexers are passive optical multiplexers and demultiplexers, enabling distribution of multiple optical signals at different wavelengths through a single optical fibre network distribution. Suitable for Fracarro Home Fibre systems as well as other WDM installations.



CWDM 5	
Fracarro code	287341 (MUX) 287342 (DEMUX)
Optical connectors	SC/APC
Wavelength	1310, 1510, 1530, 1550, 1570
CWDM 2	
Fracarro code	287343 (MUX-DEMUX)
Optical connectors	SC/APC
Wavelength	1310, 1550

Receivers

Our range of optical receivers include **several options**, tailored to different system requirements: from the Quad with 4 universal outputs for direct connection to the TV, to the Quattro with five independent outputs (HL, VL, HH, VH and TV) for multiswitch systems. There is also a version available with a single terrestrial output.



OPT-RX DT


Fracarro code	270693	
Optical input	No.	1 SC/APC
RF outputs	No.	4 universal TV/SAT

OPT-RX DT Quattro

Fracarro code	270695	
Optical input	No.	1 SC/APC
RF outputs	No.	5 (4 SAT polarities + 1 TERR)

OPT-RX TV

Fracarro code	270696	
Optical input	No.	1 SC/APC
RF outputs	No.	1 TERR



4 SAT + DVB-T over one fibre