


Compact Msw 9 IN A/P TV

SWP908TS SWP912TS SWP916TS SWP924TS SWP932TS



The **SWP9xxTS Serie** belongs to the **compact** multiswitch range with **9 inputs** (8 satellite polarities and TV); it was designed to fulfil every installation requirement in small and medium distribution systems.

The product ensures high quality in a **compact size**, its inputs are distinguished by different **colours** to make the cable connection faster and easier.


The serie is composed by 5 products: **9 inputs with 8, 12, 16, 24 and 32 output taps**; each port has a **LED** which shows the correct reception of the STB DiSEqC command.

The product can be used with **SWA930TS** amplifier, which allows to adjust appropriately the satellite and TV gains.

Characteristics

- **Dip switch** to select **TV** gain active and passive
- **Return channel** included when TV gain is passive
- Satellite bandwidth up to **2300MHz**
- **High output level**
- **Standalone power supply** for easier installation; it provides the required voltage to the LNB
- Easy to install thanks to **standard colour coding**
- **Low cost**
- **Compact size**

		SWP908TS	SWP912TS	SWP916TS	SWP924TS	SWP932TS
Fracarro Code		287350	287351	287352	287353	287354
Inputs		9				
Outputs		8	12	16	24	32
Satellite						
Bandwidth	MHz	950 - 2300				
Gain	dB	2	1	1	-1	-2
Uptilt	dB	4				
Max Output Level (IM3)	dBμV	100				
Return Loss	dB	10				
Terrestrial						
Bandwidth	MHz	50 - 862				
Gain Active	dB	1	0	-1	-2	-4
Gain Passive	dB	-19	-20	-21	-22	-24
Max Output Level (IM3)	dBμV	95				
Return Loss	dB	10				
General Parameters						
Isolation SAT/SAT TV/SAT	dB	30				
Standard	V, KHz	14/18 0/22 - DiSEqC 2.0				
Tap Consumption	mA	50				
DC Plug	mm	2.1x5.5x12				
	pol	internal positive, external negative				
Max current to LNB	mA	2000				
Dimensions	mm	110x190x40	170x190x40	170x190x40	230x190x40	300x190x40
Operating Temperature	°C	-20 ÷ 60				

Power Supply						
Output Voltage	V	13				
Output Current	mA	1500				
Main Voltage	V, Hz	120-240, 50-60				
Isolation	Classe	II				
DC Plug	mm	2.1x5.5x12				
	pol	 internal positive, external negative				
Dimensions	mm	90 x 70 x 45				
Operating Temperature	°C	0 ÷ 40				

Code	Item	Packaging	Quantity	Dimensions	Net Weight	Weight
			pcs	mm	kg	kg
287350	SWP908TS	Single	1	255x245x55	0.8	0.8
287351	SWP912TS	Single	1	330x245x55	1.1	1.1
287352	SWP916TS	Single	1	330x245x55	1.1	1.1
287353	SWP924TS	Single	1	390x255x50	1.2	1.2
287354	SWP932TS	Single	1	390x255x50	1.4	1.4
	Power Supply	Single	1	65x130x55	0.3	0.3

Installation Example

