



Enjoy digital cable television in HD

Connect the THC300 to your HDTV and enjoy digital cable TV in best HD quality. Digital surround sound is granted for when connected to a digital audio amplifier. Enjoy great sound in Dolby® Digital Plus* and play back multimedia files via USB. Further great features are the electronic programme guide, timer functions, favourite lists for individual sorting of your preferred TV and radio programmes, subtitling, teletext and much more.

 $^\star \text{Dolby}$ and the double-D symbol are registered trademarks of Dolby Laboratories.

Evolution. Emotion. Passion.

www.thomsonstb.net















Digital HD Cable Receiver


Enjoy digital cable television in HD

THC300

- ▶ HDTV receiver for digital Free-to-Air TV and radio programmes via cable(1)
- Quick and easy installation & user-friendly menu
- Excellent audio and video quality
- ▶ USB port for playback of multimedia files⁽²⁾ and receiver software updates via USB storage device
- Supports Dolby® Digital Plus⁽³⁾
- ► Electronic TV Programme Guide (EPG) for on screen programme information of present/ following event information up to 7 days(4)
- Booking of events directly from EPG
- ▶ 8 favourite lists for TV and radio programmes
- ▶ 8 event timers with 4 modes (once, daily, weekly, monthly)
- ▶ 1000 channels memory capacity
- Digital sound via coaxial output (S/PDIF) by connecting to digital amplifier
- High definition on screen display (OSD)
- Automatic and manual channel scan options
- Parental lock function for menu



- Teletext, full multi-lingual DVB subtitling and audio track support(4)
- Multi-lingual support on screen menu (OSD)
- USB power control for power saving in standby mode
- User-friendly remote control
- Fast channel zapping
- Channel handling options: lock, edit, move, sort, skip, delete and rename
- Power on with last viewed channel
- Power saving automatic standby function
- Connectors: Cable IN, Cable OUT, S/PDIF (coaxial), HDMI, TV SCART, USB
- Accessories: Remote control, 2x AAA batteries



Tuner: Sony CXD2872 Input Impedance: 75 Ohm ... Minimum Input Level: ≤ 40 dBuv (64 QAM) ≤ 44 dBuv (256 QAM)

Receiving Channel Range: 46 MHz ~ 862 MHz Modulation: 64 QAM/256 QAM

Symbol rate: 3.6 M ~ 6.952 MS/s (64 QAM)

Video decoder: MPEG -2 MP@HL, AVC/H.264 HP@L4.1, MPEG-4 ASP supported

Video resolution: 480i, 480p, 576i, 576p, 720p, 1080i, 1080p, By Source, By Native TV,

Decoding & Video Out: PAL Aspect ratio: 4:3 Letterbox, 4:3 Pan & Scan, 16:9, Auto

Audio:

Audio support: AAC/AC3+/PCM/ Audio mode: Stereo, Mono

Transponder: DVB-C (Digital Cable)

Main Processor: Ali M3812 Demodulator: Sony CXD2837 Memory: DDR II 64 MB FLASH size: 4 MB

Connectors

Cable IN - IEC Female Cable OUT - IEC Male (Loop through) S/PDIF (coaxial) **HDMI** TV SCART

USB 2.0 port : DC 5 V, 800 mA (max.) supported

General Data:

Supply voltage: 220 - 240 V AC (SMPS), 50/60 Hz Power consumption: 5.14 W (typ.) 12 W (max.) Power consumption in standby: max. 0.7 W Operating temperature: 0 ~ +40 °C Storage temperature: -10 ~ +50 °C Operating humidity range: 10 ~ 85%, RH, Non-condensing

Weight in kg: 0.34

Size (WxDxH) in mm: 168 x 105 x 40

199 416 006

*Dolby and the double-D symbol are registered trademarks of Dolby Laboratories.

Connecting to:

- 1. Cable
- 2. TV/receiver (coax.)
- 3. Digital audio amplifier (coax.)
- 4. TV (HDMI)
- 5. TV (SCART)
- 6. Power cord

THC300 FAN: 8717185448627

local signal conditions.

Signal conditions of all files although extensions are listed, as it depends data bit are the playback of all files although extensions are supported). double—by symbol are registered trademarks of Dolby Laboratories. and on broadcaster.



0820 400 044 € 0.12/Min., österr, Festnetz +359 32 634451 support_bg@thomsonstb

0180 599 96 25 DK support_dk@thomsonstb.net NL support_nl@thomsonstb.net

0826 461 062 € 0.15 par mn poste fixe en France 801 702 027

+36 1 445-26-10

+380(44)228-24-73